

# Passive Road Surface Temperature Sensor

The surface temperature sensor measures runway and highway-temperatures highly precise, both on asphalt and concrete.

Works also in conjunction with ARS31pro.

Passive Road Surface Temperature Sensor			Order No.
<b>WST1</b> 50m cable length			<b>8160.WST1</b>
<b>Technical Data</b>	Dimensions	Ø 60 mm, height 40 mm	
	Weight	approx. 150 g	
	Storage temperature	-40 ... 70 °C	
	Protection type	IP68	
	Op. temperature range	-40 ... 70 °C	
<b>Temperature/NTC</b>	Measuring range	-40 ... +70 °C	
	Accuracy	±0,3 °C ( -10...+10°C) otherwise ±1,0 °C	

Passive Road Surface Temperature Sensor			Order No.
<b>WST2</b> 50m cable length			<b>8160.WST2</b>
<b>Technical Data</b>	Dimensions	Ø 60 mm, height 40 mm	
	Weight	approx. 150 g	
	Storage temperature	-40 ... 70 °C	
	Protection type	IP68	
	Op. temperature range	-40 ... 70 °C	
<b>Temperature/PT100</b>	Measuring range	-40 ... +70 °C	
	<b>1/3 DIN B</b> Accuracy	±0,1 °C @ 0°C	

The runway/road surface temperature sensor 8160.WST1 can be connected with any WS family sensor of Lufft UMB technology.

The runway/road surface temperature sensor 8160.WST2 can be used with Luffts UMB-ANACON converter.

